




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>3</sup> :</b>  <b>A61M 15/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 82/ 01470</b>  <b>(43) International Publication Date:</b> 13 May 1982 (13.05.82)
<b>(21) International Application Number:</b> PCT/US81/01457 <b>(22) International Filing Date:</b> 28 October 1981 (28.10.81)  <b>(31) Priority Application Number:</b> 80/34867 <b>(32) Priority Date:</b> 30 October 1980 (30.10.80) <b>(33) Priority Country:</b> GB  <b>(71) Applicant (for all designated States except US):</b> RIKER LABORATORIES, INC. [US/US]; 19901 Nordhoff Street, Northridge, CA 91324 (US).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> BAUM, Eric, Arthur [GB/GB]; Minnesota 3M Research Limited, Pinnacles, Harlow, Essex (GB). KIRK, William, Francis [GB/GB]; Riker Laboratories, Inc., 1 Morley Street, Loughborough, Leicestershire (GB). MEREDITH, William, George [GB/GB]; 95 Swithland Lane, Rothley, Leicestershire (GB). TANSEY, Ian, Phillip [GB/GB]; 75 Cotes Road, Barrow-on-Soar, Leicestershire (GB). WASS, Anthony, Charles, Lammond [GB/GB]; The Mousehole, Duddington, Stamford, Lincolnshire (GB).		<b>(74) Agents:</b> HUEBSCH, William, L. et al.; Office of Patent Counsel, Minnesota Mining and Manufacturing Company, 3M Center, P. O. Box 33427, St. Paul, MN 55133 (US).  <b>(81) Designated States:</b> AT (European patent), AU, BR, CH (European patent), DE (European patent), DK, FI, FR (European patent), GB (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent), US.  <b>Published</b> <i>With international search report.</i>

**(54) Title:** POWDER INHALATION DEVICE**(57) Abstract**

An inhaler device for administering powdered medicaments from within a container having two halves. The device is designed to assist the user in separating the two halves of the container and to provide an optimum air flow pattern through a chamber in which the separated container half is positioned to afford dispersion of the powder medicament. The inhaler device comprises a body (10) having walls defining a chamber (16), an inlet port (29) into the chamber for the entry of air, and a mouthpiece (18) having a central through opening (19) communicating with the chamber. Manually-activatable means (20) mounted on the body of the device convey a first portion (12) of the container (11) from a first position spaced from the chamber to a predetermined dispense position within the chamber with an open end of the first capsule portion uppermost so that airflow into the inlet port and through the chamber induced by suction at the mouthpiece will cause the powdered medicament in the first container portion to become entrained in the airflow; and manually-activated means (4) mounted on the body remove a second container portion (14) to open the container prior to positioning of the first container portion at the dispense position.



***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	KP	Democratic People's Republic of Korea
AU	Australia	LI	Liechtenstein
BR	Brazil	LU	Luxembourg
CF	Central African Republic	MC	Monaco
CG	Congo	MG	Madagascar
CH	Switzerland	MW	Malawi
CM	Cameroon	NL	Netherlands
DE	Germany, Federal Republic of	NO	Norway
DK	Denmark	RO	Romania
FI	Finland	SE	Sweden
FR	France	SN	Senegal
GA	Gabon	SU	Soviet Union
GB	United Kingdom	TD	Chad
HU	Hungary	TG	Togo
JP	Japan	US	United States of America

## POWDER INHALATION DEVICE

Technical Field

This invention relates to devices which facilitate the inhalation of powdered medicaments.

5 Background Art

There are many devices which facilitate the inhalation of powdered medicaments by the use of propellants, such as compressed or liquified gases, to dispense and disperse the medicament. These devices may be complex  
10 to construct and have the disadvantage that in order for the optimum effect to be obtained it is essential that inhalation and dispensing be synchronous.

There are also a number of known breath-actuated inhalation devices for administering powdered medicaments  
15 to the lungs. The powdered medicament is typically supplied in commercially available capsules which comprise first and second capsule portions, each including a tubular part having an open end and an end wall opposite its open end, with the open end and tubular part of one  
20 portion being received through the open end of the other and the tubular parts in mechanical or frictional engagement to retain the powdered medicament therein. In the simpler breath-actuated devices the capsule is opened prior to insertion into the device and one capsule portion  
25 containing the medicament or the medicament itself is positioned in the device such that during inhalation through the mouthpiece the medicament becomes entrained in the air stream and passes to the patient. Examples of such devices are disclosed in British Patent Specifications Nos.  
30 1,520,064; 1,504,441; 1,118,341; 1,520,063 and 1,520,062. These devices suffer from the disadvantage that medicament may be spilled when the capsule is opened prior to insertion in the device.

British Patent Specifications Nos. 1,521,000; 1,520,062; 1,472,650 and 1,502,150 disclose more complex devices in which the complete capsule is inserted into the device, thus ensuring no spillage of medicament prior to inhalation, and access to the medicament is gained by piercing the capsule or cutting it in half inside the dispensing device. On inhalation the air flows into or through the capsule and the powder within is entrained in the air stream and carried towards the mouth.

The devices disclosed in British Patent Specifications Nos. 1,485,163; 1,331,216; 1,457,352; 1,396,258; 1,182,779; 1,404,338; 1,459,426 and 1,118,341 and United States Patent Specifications Nos. 4,117,844 and 4,116,195 are designed to agitate the capsule containing the medicament in order to help release and disperse the powder from the capsule. The capsule may be agitated by various means, including creating a turbulent air flow, or by rotating and/or vibrating the capsule through the use of vanes or propellers. These devices are complex and are often difficult to operate.

United States Patent Specification No. 4,210,140 discloses a device in which access to the powdered medicament is gained by pulling the capsule portions apart so that the medicament is emptied to a suitable position for entrainment in the air flow caused by inhalation.

Our copending PCT Publication No. 81/01243 discloses breath-actuated devices for the oral inhalation of powdered medicaments. Those devices each comprise a chamber having at least one inlet port for the entry of air and in direct communication with a mouthpiece; means within the chamber for holding a capsule containing a medicament substantially vertically; and means for separating the capsule portions within the chamber to expose the open end of the lowermost capsule portion and afford access to the powdered medicament within in a position such that when the device is operated by suction at the mouthpiece, air flows essentially transversely across the

open end of the lowermost capsule portion, causing the particles of powdered medicament therein to become entrained in the air.

The devices described in that application are  
5 easy and simple to use, reduce the possibility of the user  
spilling the medicament and ensure that any medicament  
that is spilled will still be inhaled, and are very  
efficient when compared to breath-actuated devices of the  
prior art. Positioning the means for separating the  
10 capsule portions in the chamber, however, presents  
possibilities for air leaks into the chamber, and  
restricts the design possibilities to provide a desired  
air flow pattern through the chamber.

#### Disclosure of Invention

15 The present invention provides a breath-actuated  
device which facilitates the inhalation of powdered medica-  
ments from within a container such as a capsule, which  
device both includes a mechanism to assist the user in  
separating portions of the container and allows the device  
20 to provide an optimum air flow pattern through a chamber  
in which the separated container portion is positioned to  
afford dispersion of the powder.

According to the present invention there is pro-  
vided a device facilitating the inhalation of powdered  
25 medicaments from within a container comprising a first  
container portion adapted to contain the powder and having  
an open end, and a second container portion closing the  
open end in the first container portion. The device  
comprises a body having walls defining a chamber, at least  
30 one inlet port into the chamber for the entry of air, and  
a mouthpiece having a central through opening  
communicating with the chamber. A manually-activatable  
means mounted on the body is provided for conveying the  
first container portion from a first position spaced from  
35 the chamber to a predetermined dispense position within  
the chamber with the open end of the first container



portion uppermost so that airflow into the inlet port and through the chamber induced by suction at the mouthpiece will cause the powdered medicament in the first container portion to become entrained in the airflow. Also provided  
5 is a manually-activatable means mounted on the body for removing the second container portion from the first container portion prior to positioning of the first container portion at the dispense position by the means for conveying (i.e., prior to or during movement of the  
10 first container portion to the dispense position).

Devices according to the present invention can be adapted to receive containers in the form of conventional capsules used in the pharmaceutical industry which, as described above, comprise first and second capsule  
15 portions each including a tubular part having an open end and an end wall opposite its open end, with the open end and tubular part of one portion being received through the open end of the other and the tubular parts in frictional or mechanical engagement to retain the powdered medicament  
20 therein. Alternatively, however, devices according to the present invention can be adapted for use with containers of other shapes in which access to powder in a first container portion is gained by displacing a second container portion from an opening of the first container portion  
25 (e.g., by displacing a second container portion in the form of a bung or an adhered or crimped foil lid from an open end of a first container portion of any suitable shape); or which may have the first container portion integrally formed in a movable portion thereof providing  
30 the means for conveying, with a wall of the body of the device providing the second container portion or with the second container portion being provided by a foil lid over the open end of the first container portion.

The means for conveying the first portion of the  
35 container in a device according to the present invention can comprise a generally cylindrical support member rotatably mounted on the body of the device which is



adapted to convey a number of first container portions  
seriatim from the first to the dispense position. Where  
such a device is adapted for use with conventional  
capsules of the type described above, the support member  
5 may have a plurality of radially-extending sockets opening  
through its periphery with each of the sockets being  
adapted to receive and hold the first portion of one of  
the capsules with the second portion of the capsule  
projecting radially outwardly of the support member. The  
10 means for removing the second capsule portion may comprise  
an extractor having at least one gripping wall with a  
surface adapted to engage the second capsule portion,  
which extractor is mounted on the housing for movement  
between a raised position with the gripping wall spaced  
15 from a capsule in the support member at the first  
position, and an engage position with the gripping wall in  
engagement with the second portion of a capsule in the  
support member at the first position.

Further, the device may include coupling means  
20 engageable between the support member and the extractor  
for moving the support member to convey an opened first  
capsule portion from the first position to the dispense  
position during movement of the extractor from its engage  
to its raised position. This coupling means can be a  
25 ratchet assembly comprising a wheel having teeth about its  
periphery coaxially attached to the support member, and a  
pawl coupled to the extractor and adapted to engage and  
advance the wheel upon movement of the extractor from its  
engage to its raised position.

30 The extractor can be a separate member movably  
mounted on the body, or can be incorporated in a cover for  
the device pivotably mounted on the body and having a  
portion positioned over the opening in the mouthpiece to  
close the opening when the extractor is in its engage  
35 position; but which portion is positioned away from the  
mouthpiece when the extractor is in its raised position.

The inlet ports and chamber can be arranged to



provide an airflow which is directed generally transversely across the open end of the first container portion and not substantially into the first container portion. This airflow pattern is effective in entraining powder from the container possibly due to a resonance effect produced in the container in a manner similar to the resonance produced by blowing over the top of an open bottle. Tests which have been conducted reveal that for airflow patterns generally transversely across the open end of the first portion of a capsule there tends to be an optimum position for the open end of the first capsule portion relative to the surface defining the lower side of the inlet ports. This optimum position may vary according to the capsule portion dimensions and the amount of medication in the capsule portion. It does not tend to be critical for capsule portions which are relatively shallow, (e.g., up to 10 mm), but becomes more critical when deeper capsule portions are used. In general it has been found that the open end of the capsule should not extend significantly above the surface defining the lower side of the inlet port and is preferably at the same level or slightly lower than the surface defining the lower side of the inlet port so that the medicament in the capsule portion is spaced slightly below the mainstream of the airflow. PCT Publication No. 81/01243, incorporated herein by reference, discloses further details of the relative positions of air inlets, capsule portion and mouthpieces together with experimental results.

The device according to the present invention can also be designed so that a portion or all of the airflow through the chamber enters the first container portion to scour the powdered medicament therefrom. In one embodiment which uses capsules and incorporates that feature an upper surface of the chamber slopes downwardly upstream of the dispense position for the first capsule portion and slopes upwardly downstream of the dispense position with the intersection of the sloping upper



surfaces generally aligned with the longitudinal axis of the first capsule portion at the dispense position and closely spaced from the open end of that first capsule portion. In another such embodiment, the inlet port is  
5 positioned above the dispense position to direct substantially all of the airflow through the chamber axially into the open end of the first capsule portion and then through the mouthpiece.

The chamber should be designed so that the  
10 velocity of the air into or across the open end of the container portion is high. However, the pressure drop across the chamber in use should not be high since this would require the user to exert considerable suction at a time when he is in a distressed condition. With the  
15 present invention it is possible to achieve an adequate airflow velocity into or across the first container portion and yet cause a pressure drop across the chamber which is barely noticeable to the user. A pressure drop of up to 50 cm of water appears to be an upper limit as  
20 far as comfort to the user is concerned.

The mouthpiece is preferably short and straight and can be aligned with airflow transversely across the open end of the first container portion so that there is substantially straight airflow through the device. How-  
25 ever, the mouthpiece may be shaped or inclined with respect to airflow across the first container portion without significantly affecting the efficiency of the device providing there are no obstructions which will trap the particles entrained in the airflow. It may be advanta-  
30 geous for the cross-sectional area of the mouthpiece to increase suddenly so that any large or agglomerated particles in the powdered medicament will settle in the mouthpiece rather than deposit into the patient's mouth or nasal passages. The mouthpiece of the device may be  
35 adapted for nasal inhalation and the term "mouthpiece" as used herein includes such nasal adaptors.

Brief Description of Drawing

The invention will be further described with reference to the accompanying drawings wherein like numbers refer to like parts in the several views, and  
5 wherein:

Figure 1 is an exploded perspective view of a first embodiment of a device according to the present invention;

10 Figure 2 is a perspective view of the back side of a capsule support member shown from its front side in Figure 1;

Figures 3a through 3f are sectional views of the device of Figure 1 illustrating its operating sequence and having parts broken away to show details;

15 Figure 4 is a sectional view of a second embodiment of a device according to the present invention;

Figure 5 is a sectional view of a third embodiment of a device according to the present invention;

20 Figure 6 is a fragmentary sectional view taken approximately along line 6-6 of Figure 5;

Figure 7 is an exploded view of a fourth embodiment of a device according to the present invention;

Figure 8 is a sectional view of the device of Figure 7; and

25 Figure 9 is a fragmentary sectional view of a fifth embodiment of a device according to the present invention.

Detailed Description

30 Referring now to Figures 1, 2 and 3a through 3f, there is illustrated a first embodiment of a device according to the present invention, generally designated by the reference numeral 10.

The device 10 is adapted to facilitate oral inhalation of powdered medicaments from within a container  
35 in the form of a capsule 11 of the commercially available type comprising first and second container or capsule

portions 12 and 14, each of which capsule portions 12 and 14 includes a cylindrically tubular part having an open end and a hemispherical end wall opposite its open end, with the open end and tubular part of one capsule portion 5 being received through the open end of the other and the tubular parts being in engagement to retain the powdered medicament therein. Generally the device comprises a body 15 having walls partially defining a chamber 16 free of obstructions, at least one air inlet port 17 into the 10 chamber 16, and a mouthpiece 18 having a central through opening 19 communicating directly with the chamber 16. Manually-activatable means in the form of a generally cylindrical capsule support member 20 is mounted on the body 15 for rotation about a post 22 to convey the first 15 capsule portion 12 from a first position (Figure 3c) spaced from the chamber 16 to a predetermined dispense position (Figure 3d) within the chamber 16 (which chamber 16 is partially defined by the periphery of the support member 20). In the dispense position the support member 20 20 positions the open end of the first capsule portion 12 uppermost so that airflow into the inlet port 17 and through the chamber 16 induced by suction through the mouthpiece 18 will flow substantially transversely across the open end and cause the powdered medicament in the 25 first capsule portion 12 to become entrained in the airflow. Manually-activatable means in the form of an extractor 23 slidably mounted on the body 15 is provided for removing the second capsule portion 14 prior to positioning of the first capsule portion 12 at the dispense 30 position by movement of the support member 20 (Figures 3b and 3c).

The body 15, which is preferably injection-molded of a suitable polymeric material, comprises a main portion 24 having walls, including a circular side wall 35 from which the post 22 projects, which walls define a generally cylindrical cavity in which the capsule support member 20 and extractor 23 are mounted; and a side portion



25 hinged to the main portion 24 via a flexible hinge portion 26 which comprises a circular side wall from which centrally projects a cylindrical tube 27. The inner surface of the tube 27 is adapted to frictionally engage around the post 22 to retain the capsule support member 20 and extractor 23 within the cavity, and retain together the main and side portions 24 and 25 of the body 15. Also included in the body 15 is a cover 28 mounted at one end via a thin portion of the body 15 for pivotal movement between an open position spaced from the end of the mouthpiece 18 and an opening 29 in an edge wall of the body 15 through which an end portion 30 of the extractor 23 is received and guided (Figures 1, 3b, 3c and 3d); and a closed position (Figure 3a) with a part of the cover 28 extending across the opening 29 and a distal hook-like portion 31 of the cover 28 extending across the mouthpiece opening 19, at which closed position the cover 28 is releasably retained by engagement of the upper edge of the mouthpiece 18 in a notch in the hook-like portion 31.

20           The capsule support member 20 comprises a circular side wall 32 with a central opening in which the post 22 is received; a cylindrical peripheral wall 33 with spaced orifices opening through the peripheral wall 33 through which orifices the smaller diameter second portions 14 of the capsules 11 may project; and radially-extending walls 34 projecting normally from the side wall 33 which together with parts of the peripheral wall 33 around the orifices define radially extending side entry sockets that receive and hold the larger diameter second portions 12 of the capsules 11 with their open ends at the orifices in the peripheral wall 33. Rotation of the support member 20 causes capsules 11 to move seriatim from an arcuate storage area 35 defined by portions of the body 15 and support member 20 to the first position as the preceeding capsule 11 is opened and its first portion 12 is moved to the dispense position. A projection 37 is formed on the support member 20. The projection 37 will move to the

first position as the first portion 12 of the last unused capsule 11 in the device 10 moves to the dispense position and will interfere with operation of the extractor 23 and closing of the cover 28 to signal to a user that all the capsules 11 in the device 10 have been used (Figure 3f). A toothed wheel 36 is coaxially formed on the side wall 32 opposite the walls 34 (Figure 2); which toothed wheel 36 forms a part of a ratchet assembly that provides coupling means engageable between the support member 20 and the extractor 23 for moving the support member 20 to convey the first portion 12 of the capsule from the first position to the dispense position during movement of the extractor 23 to remove the second portion of capsule 11 as will be further explained hereinafter.

The extractor 23 comprises the end portion 30 guided by walls defining the opening 29 in the body 15, from which end portion 30 project spaced gripping walls 38 adapted to frictionally engage the sides of the second portion 14 of a capsule 11. A generally U-shaped portion 39 of the extractor 23 projects from its end portion 30 and has opposed surfaces adapted to slide along and be guided by opposite surfaces of the toothed wheel 36. Such guidance of the extractor 23 allows it to slide radially with respect to the support member 20 between a raised position (Figure 3d) with the gripping walls 38 spaced from a capsule 11 in the support member 20 at the first position, and an engage position (Figures 3a and 3b) with the gripping walls 38 in engagement with the second portion 14 of a capsule 11 at the first position. Two undulating, flexible, resilient spring portions 40 of the extractor 23 also project from the end portion 30 along opposite sides of the U-shaped portion 39 and provide spring means between the body 15 and extractor 23 for biasing the extractor 23 to its raised position. An inwardly projecting pawl 41 is positioned at the distal end of one leg of the U-shaped portion 39 and is adapted to engage the toothed wheel 36 to act as a pawl for the



ratchet assembly and advance the capsule support member 20 so that a first capsule portion 12 is advanced from the first to the dispense position upon movement of the extractor 23 from its engage to its raised position under the influence of the spring portions 40.

Latch means are provided for releasably latching the extractor 23 in its engage position. The body 15 includes a plate-like latch portion 42 which has one end attached at the wall defining the side of the opening 29 adjacent the mouthpiece 18 and its opposite end attached at the mouthpiece 18, with the center of the latch portion 42 normally being bowed upwardly away from the wall defining the upper surface of the chamber 16. The latch portion 42 includes a lip 43 which, when the latch portion 42 is bowed upwardly, projects into the opening 29 where it can engage a ledge 44 along the end portion 30 of the extractor 23 (Figure 3b) and hold the extractor 23 in its engage position. The latch portion 42 may be manually pressed toward the wall defining the upper surface of the chamber 16 (Figure 3c) which will cause the lip 43 to deflect away from the ledge 44 and allow the extractor 23 to move to its raised position.

The operation of the device 10 will now be explained assuming the extractor 23 is initially latched in its engage position via the latch means with the gripping walls 38 of the extractor 23 engaged with the second portion 14 of a capsule 11 at the first position, and the cover 28 is in its closed position (Figure 3a). The user first opens the cover 28 by flexing the hook-like portion 31 of the cover 28 away from the mouthpiece 18 and pivots the cover 28 to its open position (Figure 3b). Next, he releases the latch means by pressing the latch portion 42 toward the wall defining the top surface of the chamber 16, which moves the lip 43 away from the ledge 44 so that the extractor 23 slides from its engaged toward its raised position under the influence of the spring portions 40. During the first part of such movement the



capsule portions 14 and 12 are pulled apart via frictional engagement of the extractor 23 with the second capsule portion 14 (Figure 3c). During a second part of such movement the pawl 41 on the extractor 23 engages the  
5 toothed wheel 36 to advance the first capsule portion 12 from the first to the dispense position. The user may then inhale through the mouthpiece 18 which causes air to enter the chamber 16 through the inlet port 17, flow transversely across the open end of the first capsule  
10 portion 12 at the dispense position to entrain powdered medicament into the air stream, and be drawn into the user's lungs. Subsequently the user may move the cover 28 to its closed position, whereupon engagement of the cover 28 with the projecting end portion 30 of the extractor 23  
15 moves the extractor 23 toward its engaged position so that the second capsule portion 14 is pushed away from the gripping walls 38 by the second portion 14 of the new closed capsule 11 at the first position (Figure 3e), after which the gripping walls 38 engage that new second capsule  
20 portion 14. There is sufficient friction between the post 22 and the capsule support member 20 so that as the extractor 23 is thus moved toward its engage position the leg of its U-shaped portion 39 supporting the pawl 41 will be deflected outwardly by sliding contact between the pawl 41  
25 and the curved outer surface of the next tooth on the toothed wheel 36 so that the pawl 41 will pass around that tooth on the toothed wheel 36 rather than turn the capsule support member 20 backwards. When the extractor 23 reaches its engaged position, the lip 43 engages the ledge  
30 44 to again releasably retain the extractor 23 in that position. The hook-like end portion 31 of the cover 28 again releasably engages the end of the mouthpiece 18 to retain it closed and the device 10 is ready to be used again.

35 Referring now to Figure 4, there is illustrated a second embodiment of a device according to the present invention, generally designated by the reference numeral 50.

Like the device 10, the device 50 is adapted to facilitate oral inhalation of powdered medicaments from within a container in the form of a capsule 11 of the commercially available type described above comprising

5 first and second container or capsule portions 12 and 14, and comprises a body 51 having walls partially defining an unobstructed chamber 52, at least one air inlet port 53 into the chamber 52 and a mouthpiece 54 having a central through opening 55 communicating directly with the chamber

10 52. Also, as in the device 10, manually-activatable means in the form of a generally cylindrical capsule support member 56 is rotatably mounted on the body 51 to convey the first capsule portion 12 from a first position spaced from the chamber 52 to a predetermined dispense position

15 within the chamber 52 (which chamber 52 is partially defined by the periphery of the support member 56), and in the dispense position the support member 56 positions the open end of the first capsule portion 12 uppermost so that airflow through the inlet port 53 and the chamber 52

20 induced by suction through the mouthpiece 54 will flow substantially transversely across the open end and cause the powdered medicament in the first capsule portion 12 to become entrained in the airflow. Also, manually-activatable means is provided for removing the second capsule

25 portion 14 prior to positioning of the first capsule portion 12 at the dispense position by movement of the support member 56, however unlike in the device 10, these means are provided by a wall or extractor 57 having a surface defining an opening and adapted to frictionally

30 engage the second portion 14 of the capsule 11, which extractor 57 is incorporated into a cover 58 for the device 50.

The body 51 has walls defining a generally cylindrical cavity in which the capsule support member 56

35 is mounted for rotation about a post 66 included in the body 51. The cover 58 is integrally molded with the body 51 and is pivotably mounted at one end via a thin portion





of the body 51 for pivotal movement between an open position spaced from the end of the mouthpiece 54 at which the extractor 57 is in a raised position spaced from an opening 59 in an edge wall of the body adjacent the first position; and a closed position at which the extractor 57 is in an engage position in the opening 59 and is engaged with the second portion 14 of a capsule 11 at the first position, and a hook-like distal portion 60 of the cover 58 extends across and closes the mouthpiece opening 55 and is releasably retained there by engagement of a lip 61 on the distal portion 60 with the lower edge of the mouthpiece 54.

The capsule support member 56 comprises a circular side wall 67 with a central opening in which the post 66 is received; a cylindrical peripheral wall 62 with spaced orifices opening through the peripheral wall 62 through which orifices the smaller diameter second portions 14 of the capsules 11 may project; and radially extending walls projecting normally from the side wall 67 which together with posts of the peripheral wall 62 around the orifices define radially extending side entry sockets that receive and hold the larger diameter second portions 12 of the capsules 11 with their open ends at the orifices. Rotation of the support member 56 causes capsule 11 to move seriatim from an arcuate storage area 63 defined by portions of the body 51 and support member 56, to the first position as a preceeding capsule 11 is opened and its first portion 12 is moved to the dispense position. A toothed wheel 64 is coaxially formed on one side of the support member 56, and with a pawl 65 fixed to and projecting from the cover 58 forms a ratchet assembly that provides coupling means engageable between the support member 56 and the extractor 57 for moving the support member 56 to convey the first portion 12 of the capsule from the first position to the dispense position during movement of the extractor 57 from its engage to its raised position (which occurs as the cover 58 is opened).



The operation of the device 50 will now be explained assuming that initially the cover 58 is closed so that the extractor 57 on the cover 58 is in its engage position and engaged with the second portion 14 of a capsule 11 at the first position. The user first opens the cover 58 by flexing the hook-like portion 60 of the cover 58 away from the mouthpiece 54 and pivots the cover 58 to its open position which moves the extractor 57 on the cover 58 from its engaged toward its raised position. During the first part of such movement the portions 14 and 12 of the capsule 11 at the first position are pulled apart via frictional engagement of the extractor 57 with the second capsule 14, and during a second part of such movement the pawl 65 on the cover 58 engages a tooth on the toothed wheel 64 to advance the open first capsule portion 12 from the first to the dispense position. The user may then inhale through the mouthpiece 54 which causes air to enter the chamber 52 through the inlet port 53, flow generally transversely across the open end of the first capsule portion 12 at the dispense position to entrain powdered medicament into the air stream, and be drawn into the user's lungs. Subsequently the user may remove the separated second capsule portion 14 from the extractor 57 and close the cover 58 so that extractor 57 engages the second portion 14 of the new capsule 11 at the first position. There is sufficient friction between the capsule support member 56 and the post 66 on which it is rotatably mounted so that as the cover 58 is closed the pawl 65 and the next tooth on the toothed wheel 64 deflect past each other because of the angular relationship of their surfaces that contact rather than causing the capsule support member 56 to turn backwards. When the extractor reaches its engaged position, the lip 61 engages the mouthpiece 54 to again releasably retain the cover 58 closed, and the device 50 is ready to be used again.

When the device 50 has been used a sufficient



number of times that the first portion 12 of the last un-used capsule 11 in the support member 56 has been moved to the dispense position, a disproportionately wide space 68 between successive teeth on the toothed wheel 64 will be positioned adjacent the pawl 65 on the cover 58. The space 68 is sufficiently wide that upon subsequent closing of the cover 58 the pawl 65 will not contact and deflect by the next tooth on the toothed wheel 64. The freedom of cover movement thus produced will signal the user that the device 50 is empty.

Referring now to Figures 5 and 6, there is illustrated a third embodiment of a device according to the present invention, generally designated by the reference numeral 70.

Like the devices 10 and 50, the device 70 is adapted to facilitate oral inhalation of powdered medicaments from within a container in the form of a capsule 11 of the commercially available type described above comprising first and second container or capsule portions 12 and 14; and comprises a body 71 having walls partially defining a chamber 72, at least one air inlet port 73 into the chamber 72 and a mouthpiece 74 having a central through opening 75 communicating directly with the chamber 72. Also, as in the device 10 and 50, manually-activatable means in the form of a generally cylindrical capsule support member 76 is rotatably mounted on the body 71 to convey the first portion 12 of the capsule 11 from a first position spaced away from the chamber 72 to a predetermined dispense position within the chamber 72 (which chamber 72 is partially defined by the periphery of the support member 76), and in the dispense position the support member 76 positions the open end of the first capsule portion 12 uppermost so that airflow into the inlet port 73 and through the chamber 72 induced by suction through the mouthpiece 74 will cause the powdered medicament in the first portion 12 to become entrained in the airflow. As in the device 50, manually-activatable



means in the form of a wall or extractor 77 having a surface defining an opening and adapted to frictionally engage the second capsule portion 14 is incorporated into a cover 78 for the device 70 and removes the second capsule portion 14 prior to positioning of the first capsule portion 12 at the dispense position by the means for conveying.

The body 71 has walls defining a generally cylindrical cavity in which the capsule support member 76 is mounted for rotation about a post 82 included in the body 71. The cover 78 is integrally molded with the body 71 and is mounted thereon for pivotal movement between an open position spaced from the end of the mouthpiece 74 at which the extractor 77 is in a raised position spaced from an opening 79 in an edge wall of the body adjacent the first position; and a closed position at which the extractor 77 is in an engage position in the opening 79 and is frictionally engaged with the second portion 14 of a capsule 11 at the first position, and a hook-like distal portion 80 of the cover 78 extending across and closing the mouthpiece opening 75 and releasably retained there by engagement of the upper edge of the mouthpiece 74 in a notch in the hook-like cover portion 80.

The capsule support member 76 comprises a cylindrical peripheral wall 83 with spaced orifices through which the second portions 14 of capsules 11 can project that open into radially extending sockets in the support member 76 in which the first portions 12 of capsules 11 are held and retained in the same manner as they are held and retained in the support members 20 and 56 of the devices 10 and 50. Rotation of the support member 76 causes capsules 11 to move seriatim from an arcuate storage area 81 defined by portions of the body 71 and support member 76 to the first position as a preceeding capsule 11 is opened and its first portion 12 is moved to the dispense position. A toothed wheel 84 is coaxially formed on one side of the support member 76 and with a



pawl 85 projecting from and fixed to the cover 78 forms a ratchet assembly that provides coupling means engageable between the support member 76 and the extractor 77 on the cover 78 for moving the support member 76 to convey the  
5 first portion 12 of the capsule from the first position to the dispense position during movement of the extractor 77 on the cover 78 from its engage to its raised position (which occurs as the cover 78 is opened).

The device 70 is operated by a user and operates  
10 in essentially the same manner described above with respect to the device 50 and only differs significantly from that device by the shape of an inner surface of the upper wall defining the chamber 72. In the device 70 that  
15 part 87 of inner surface from the air inlet port 73 to the dispense position slopes downwardly, whereas a part 88 of that inner surface from the dispense position toward the mouthpiece 54 slopes upwardly. A longitudinal axis 89 of  
20 the first capsule portion 12 at the dispense position is aligned with the intersection of the sloping surface parts 87 and 88, and that intersection is above and close to the open end of the first capsule portion 12 at the dispense position. This arrangement causes some of the air inhaled  
25 through the chamber 72 to flow into the first capsule portion 12 and scour the powdered medicament therefrom. As a non-limiting example, good results have been achieved when the angle between the surface part 87 and the axis  
30 89 is about 55°, the angle between the surface part 88 and the axis 89 is about 75°, and the intersection of the surface parts 87 and 88 is located about 1 millimeter above the open end of the first capsule portion 12. In general, both of the angles described above should be less than 80 degrees.

Referring now to Figures 6 and 7, there is illustrated a fourth embodiment of a device according to  
35 the present invention, generally designated by the reference numeral 90.

Like the devices 10, 50 and 70, the device 90 is



adapted to facilitate oral inhalation of powdered medications from within containers comprising first and second container portions 92 and 93; and comprises a body 94 having walls partially defining an unobstructed chamber 95, at least one air inlet port 96 into the chamber 95, and a mouthpiece 97 having a central through opening 98 communicating directly with the chamber 95. As in the devices 10, 50 and 70, manually-activatable means in the form of a generally cylindrical container support member 99 is rotatably mounted on the body 94 to convey the first container portion 92 from a first position spaced from the chamber 95 to a predetermined dispense position within the chamber 95 (which chamber 95 is partially defined by the periphery of the support member 99), and in the dispense position the support member 99 positions the open end of the first container portion 92 uppermost so that airflow into the inlet port 96 and through the chamber 95 induced by suction through the mouthpiece 97 will flow generally transverse of the open end of the first container portion 92 and cause the powdered medicament in the first container portion 92 to become entrained in the airflow. Also as in the devices 10, 50 and 70, manually-activated means is provided for removing the second container portion 93 prior to positioning of the first container portion 92 at the dispense position by the support member 99.

Unlike the devices 10, 50 and 70, however, the support member 99 of the device 90 has a plurality of the first container portions 92 integrally formed therein around its periphery, and the second container portion 93 is a wall on the body 94 that closes the first container portion 92 at the first position. Manual rotation of the support member 99 via a manually engageable knob at its end, thus causes the second container portion or wall 93 to be removed from over the first container portion 92 during movement of the first container portion 92 to the dispense position.



Referring now to Figure 9, there is illustrated a fifth embodiment of a device according to the present invention, generally designated by the reference numeral 100.

5           Like the other illustrated devices, the device 100 is adapted to facilitate oral inhalation of powdered medicaments from within a container in the form of a capsule 11 comprising first and second container or capsule portions 12 and 14; and comprises a body 101  
10   having walls partially defining a chamber 102, an air inlet port 103 into the chamber 102 and a mouthpiece 104 having a central through opening 105 communicating directly with the chamber 102. Also, manually-activatable means in the form of a generally cylindrical capsule  
15   support member 106 is rotatably mounted on the body 101 to convey the first portion 12 of the capsule 11 from a first position spaced away from the chamber 102 to a predetermined dispense position within the chamber 102 (which  
20   chamber 102 is partially defined by the periphery of the support member 106), and in the dispense position the support member 106 positions the open end of the first capsule portion 12 uppermost so that airflow into the  
25   inlet port 103 and through the chamber 102 induced by suction through the mouthpiece 104 will cause the powdered medicament in the first portion 12 to become entrained in the airflow. As in the devices 50 and 70, manually-activatable means (not shown) in the form of a wall or  
30   extractor having a surface defining an opening and adapted to frictionally engage the second capsule portion 14 is incorporated into a cover for the device and removes the second capsule portion 14 prior to positioning of the first capsule portion 12 at the dispense position by the means for conveying.

35           The operation and structure of the device 100 is essentially identical to the operation and structure of the devices 50 and 70 except for the shape of the inner surface of the upper wall defining the chamber 102 and the



location of the inlet port 103. In the device 100, the inlet port 103 is positioned directly above the dispense position, and a part 108 of the upper wall of the chamber depends downwardly and is located essentially at the central axis of the second capsule portion 14 at the dispense position to direct substantially all of the airflow through the device 100 axially into one side of the first capsule portion 12 at the dispense position, and cause the airflow to change its direction of flow within the second capsule so that the powder is entrained in and flows with the air up out of the other side of the first capsule portion 12 and through the mouthpiece 104.

The devices 10, 50, 70, 90 or 100 may be made from any suitable polymeric material such as polypropylene or nylon, and at least portions of the devices may be sufficiently transparent that a user may readily determine when a first container portion is in the dispense position and how many unused containers remain in the device.

Having thus described the present invention with respect to five embodiments thereof it will be evident to those skilled in the art that many changes in the device could be made without departing from the spirit of the invention. Thus, the scope of the present invention should not be limited by the structures of the embodiments described in the specification, but only by the structures recited in the dependent claims and their equivalents.



-23-  
Claims

1. A device facilitating the inhalation of powdered medicaments from within a container of the type comprising a first container portion adapted to contain the powder and having an open end, and a second container  
5 portion closing the open end of the first container portion, said device comprising a body having walls defining a chamber, an inlet port into said chamber for the entry of air, and a mouthpiece having a central through opening communicating with said chamber; manually-  
10 activatable means mounted on said body for conveying the first container portion from a first position spaced from said chamber to a predetermined dispense position within said chamber with the open end of said first container portion uppermost so that airflow into said inlet port and  
15 through said chamber induced by suction at the mouthpiece will cause the powdered medicament in said first container portion to become entrained in the airflow; and manually activatable means mounted on said body for removing the second container portion from said first container portion  
20 prior to positioning of the first container portion at the dispense position by said means for conveying.

2. A device according to claim 1 wherein said means for conveying comprises a generally cylindrical support member rotatably mounted on said body.

25 3. A device according to claim 2 wherein said container is a capsule and the portions of said capsule each include a tubular part having an open end and an end wall opposite its open end, with the open end and tubular part of one capsule portion being received through the  
30 open end of the other and the tubular parts in engagement to retain the powdered medicament therein, and said support member has a plurality of radially extending sockets opening through its periphery with each of said sockets being adapted to receive and hold the first capsule por-  
35 tion with the second capsule portion projecting from the



socket radially of the support member, and said means for removing the second capsule portion comprises an extractor having at least one gripping surface adapted to engage said second capsule portion, said extractor being mounted  
5 on said body for movement between a raised position with said gripping surface spaced from the capsule in said support member, and an engage position with said gripping surface in engagement with the first capsule portion of a capsule in said support member at said first position.

10 4. A device according to claim 3 further including coupling means engageable between said support member and said extractor for moving said support member to convey said first capsule portion from said first position to said dispense position during movement of said  
15 extractor from said engage to said raised position.

5. A device according to claim 4 wherein said coupling means is a ratchet assembly comprising a wheel having teeth about its periphery coaxially attached to said support member, and a pawl coupled to said extractor  
20 and adapted to engage and advance said wheel upon movement of said extractor from said engage to said raised position.

6. A device according to claim 4 wherein said extractor is incorporated in a cover pivotably mounted on  
25 said body, which cover further includes a portion positioned over the opening in said mouthpiece when said extractor is in said engage position, and spaced from said mouthpiece when said extractor is in said raised position.



7. A device according to claim 4 wherein said extractor is mounted on said body for radial movement with respect to said support member between said engage and raised positions, and said device further includes a  
5 spring biasing said extractor toward said raised position, means for releasably latching said extractor in said engage position in opposition to said spring, and a cover pivotably mounted on said body for movement between an open position spaced from said mouthpiece and affording  
10 release of said means for latching and movement of said extractor to said raised position under the influence of said spring, and a closed position releasably engaged with said body with a portion of said cover over said mouth-  
15 piece, said cover being adapted to move said extractor from said raised to said engage position upon movement of said cover from said open to said closed position.


8. A device according to claim 2 wherein said cylindrical support member has a plurality of first container portions formed around its periphery having ends  
20 that open through its periphery, and said body has a wall closing the open end of each container portion when the container portion is in said first position.

9. A device according to claim 1 wherein said inlet port and chamber are shaped and arranged to provide  
25 an airflow through said chamber that is substantially transversely across the open end of said first container portion at said dispense position.


10. A device according to claim 1 wherein said chamber has an upper surface that slopes downwardly  
30 upstream of said dispense position and slopes upwardly downstream of the dispense position with the intersection of the sloping upper surfaces generally centered over the first container position at the dispense position and closely spaced from its open end to direct a portion of  
35 air flowing through said chamber into the first container portion at the dispense position.




1 / 3




**FIG. 1**




**FIG. 2**



**FIG. 3a**




**FIG. 3b**




**FIG. 3c**


**FIG. 3d**




***FIG. 3e***



**FIG. 3f**



**FIG. 7**



**FIG. 8**






FIG. 9

3 / 3



**FIG. 6**

# INTERNATIONAL SEARCH REPORT

International Application No PCT/US81/01457

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) <sup>1</sup>		
According to International Patent Classification (IPC) or to both National Classification and IPC		
INT. CL. <sup>3</sup>	A61M 15/00	
U.S. CL.	128/203.15	
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>4</sup>		
Classification System	Classification Symbols	
US	128/203.15, 266 222/4, 144, 145, 169, 630	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>5</sup>		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> <sup>14</sup>		
Category <sup>6</sup>	Citation of Document, <sup>16</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>
P	GB, A, 2,061,735 Published 20 May 1981 Riker Laboratories, Inc.	
X	US, A, 4,210,140 Published 01 July 1980 James, et al.	1,9
A	US, A, 2,587,215 Published 26 February 1952 Priestly (Figure 8)	
A	US, A, 3,870,046 Published 11 March 1975 Elliott	
A	US, A, 4,240,418 Published 23 December 1980 Rosskamp et al.	
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><sup>15</sup> Special categories of cited documents:</p> <p>"A" document defining the general state of the art</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document cited for special reason other than those referred to in the other categories</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> </div> <div style="width: 45%;"> <p>"P" document published prior to the international filing date but on or after the priority date claimed</p> <p>"T" later document published on or after the international filing date or priority date and not in conflict with the application, but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance</p> </div> </div>		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search <sup>1</sup> <div style="text-align: center; font-weight: bold;">JAN 27 1982</div>		Date of Mailing of this International Search Report <sup>2</sup> <div style="text-align: center; font-weight: bold;">01 FEB 1982</div>
International Searching Authority <sup>1</sup> <div style="text-align: center; font-weight: bold;">ISA/US</div>		Signature of Authorized Officer <sup>10</sup> 

**THIS PAGE BLANK (USPTO)**